



# Technical Data

PRODUCT TECH

©2011 Torco

## V-SERIES "SS" SYNTHETIC MOTOR OIL SAE 20W/50

### >>Description

Torco V-Series "SS" Synthetic Motor Oil is engineered utilizing Group IV/V synthetic base oil chemistries to provide the most shear stable and oxidation stable formula. Developed to resist extreme heat and loads encountered in V-type motorcycle engines. Torco V-Series "SS" Synthetic Motor Oil fortified with Torco's race specific MPZ technology, which reduces frictional losses for maximum horsepower and torque output. The V-Series line is specifically formulated for Harley® and custom v-twin engines.

### >>Features

- >Group IV/V 100% Synthetic Formulas
- >Maximizes horsepower & torque output by as much as 4%
- >Reduces engine temperatures
- >Highest level of engine protection.

### >>Application

For use in all American-made and metric V-twin motorcycle engines. Highly recommended in extreme heat, high RPM and long operations. Exceeds manufacturer warranty requirements. Exceeds API SG / JASO-MA

### >>Typical/Test Data

<b>SAE Grade</b>	<b>ASTM#</b>	20W-50
<b>Appearance</b>	<b>Visual</b>	Amber
<b>Viscosity @ 100°C</b>	<b>D-445</b>	20.98
<b>Viscosity @ 40°C</b>	<b>D-445</b>	169.26
<b>Pour Point, °C</b>	<b>D-97</b>	-39
<b>Flash Point, °C</b>	<b>D-92</b>	230

### >>Directions

Follow manufacturer's fill level requirements. Compatible with other petroleum and synthetic lubricants.

### >>Package Sizes / P/N

<b>SAE Grade</b>	20W/50
<b>1-Liter (1.056 US QT)</b>	T642050CE
<b>12/1-Liter Case</b>	T642050C
<b>5 Gallon Pail</b>	T642050E
<b>55 Gallon Drum</b>	T642050B

