



Technical Data

PRODUCT TECH

©2013 Torco

SR-1R 100% SYNTHETIC RACING OILS

SAE: 10W-30, 10W-40, 10W-60, 20W-50, 25W-60

>>Description

Torco SR-1R 100% Synthetic Racing Oils are engineered to protect engines under severe racing conditions and offers the highest level of performance and engine protection. It features a combination of Group IV and Group III base stock technology along with Torco's exclusive race proven additive chemistry, MPZ®. It provides excellent anti-wear and anti-friction of vital engine components including bearings, cams, cylinders, pistons, rings and valvetrain parts by minimizing frictional losses to deliver more horsepower and torque output. SR-1R Synthetic Racing Oils are formulated to Torco's proprietary race specific additive technology.

>>Features

- >100% Synthetic Formula utilizing a specialized combination Group IV and III technology
- >Incorporates new generation MPZ® low frictional loss technology
- >Extreme thermal stability under severe temperatures
- >Increases horsepower & torque

>>Application

Recommended from stock to highly modified street to all out race engines. Used for drags, drifting, road racing, off road etc. The proper viscosity choice allows use in supercharged, turbocharged and nitrous applications. Exceeds API category SM performance requirements and intended for racing applications.

>>Typical/Test Data

SAE Grade	ASTM#	10W-30	10W-40	10W-60	20W-50	25W-60
Appearance	Visual	Amber	Amber	Amber	Amber	Amber
Viscosity @ 100°C	D-445	11.10	13.25	25.52	19.96	24.7
Viscosity @ 40°C	D-445	64.20	86.75	177.57	138.31	190
Pour Point, °C	D-97	-37	-34	-18	-28	-18
Flash Point, °C	D-92	240	242	240	243	248

>>Directions

Follow manufacturer's fill level requirements. Compatible with other petroleum and synthetic lubricants.

>>Package Sizes / P/N

SAE Grade	10W-30	10W-40	10W-60	20W-50	25W-60
1-Liter (1.056 US QT)	A161033CE	A161044CE	A161060CE	A162055CE	A162560CE
12/1-Liter Case	A161033C	A161044C	A161060C	A162055C	A162560C
5 Gallon Pail	A161033E	A161044E	A161060E	A162055E	A162560E
55 Gallon Drum	A161033B	A161044B	A161060B	A162055B	A162560B



TORCO INTERNATIONAL CORPORATION
 9145 Milliken Avenue, Rancho Cucamonga, CA 91730
 (909) 980.1495 phone | (909) 980.1465 fax
 www.torcousa.com website | info@torcousa.com email